

KUDOS

功率可调台式超声波清洗器(加热型)

SK2210HP-SK8210HP

- 背景光液晶显示屏
  - 屏上菜单参数选择
  - 1~199分钟定时范围
  - 功率的40~100%，步进1%的连续精细可调
  - 设定温度、槽内水温屏上实时显示
  - 加热无水自动检测报警
  - 20℃~60℃的温度设定范围
  - 超声辅助均匀水温
  - 工作参数断电记忆功能
- Backlight LCD
  - Parameter selection from displayed menu
  - 1-199 minutes timing range
  - 40-100% of maximum power adjustable with subtle 1% step
  - Real-time displays of the set temperature and water temperature in the trough
  - Auto alarm and power-off upon boiling dry
  - temperature set range of 20 °C-60 °C
  - Ultrasonically water temperature harmonization
  - Last parameter memory function



主要技术指标		
工作频率	Operating Frequency	53kHz
数字定时	Digital Timer	1-199min
功率调节	Adjustable Power	功率的40-100%,步进1%的连续精细可调
设温范围	Temperature set range	20℃-60℃
电 源	Power Supply	220V/50Hz
清洗槽材料	Material of tank	304不锈钢 304 Stainless steel

Optional accessories please turn to P37



SK2210HP



SK3210HP



SK3310HP

SK2210HP		
超 声(w)	Ultrasonic	100
加 热(w)	Heater	75
容 量(L)	Capacity	3
槽内尺寸(mm)	Tank Size(L×W×H)	240×140×100
外形尺寸(mm)	External Size(L×W×H)	270×160×240
纸箱尺寸(mm)	Carton Size(L×W×H)	367×267×334
重量(kg)	Net	4
Weight	Gross	4.8
	标准配置	托架 Support rack 降音盖 Cover
价 格(RMB)	Price	3400.00

SK3210HP		
超 声(w)	Ultrasonic	150
加 热(w)	Heater	110
容 量(L)	Capacity	4.5
槽内尺寸(mm)	Tank Size(L×W×H)	300×150×100
外形尺寸(mm)	External Size(L×W×H)	330×180×240
纸箱尺寸(mm)	Carton Size(L×W×H)	405×260×335
重量(kg)	Net	4.7
Weight	Gross	5.6
	标准配置	托架 Support rack 降音盖 Cover
价 格(RMB)	Price	4600.00

SK3310HP		
超 声(w)	Ultrasonic	180
加 热(w)	Heater	150
容 量(L)	Capacity	6
槽内尺寸(mm)	Tank Size(L×W×H)	300×150×150
外形尺寸(mm)	External Size(L×W×H)	330×180×290
纸箱尺寸(mm)	Carton Size(L×W×H)	427×279×394
重量(kg)	Net	5.5
Weight	Gross	6.5
	标准配置	托架 Support rack 降音盖 Cover
价 格(RMB)	Price	4900.00





SK5210HP

SK5210HP		
超声(w)	Ultrasonic	200
加热(w)	Heater	270
容量(L)	Capacity	10
槽内尺寸(mm)	Tank Size(L×W×H)	300×240×150
外形尺寸(mm)	External Size(L×W×H)	360×270×310
纸箱尺寸(mm)	Carton Size(L×W×H)	432×367×397
重量(kg)	Net	7.3
	Gross	8.6
排水阀	Drain Valve	
标准配置	Accessories	托架 Support rack 排水软管Soft drainpipe 降音盖 Cover
价 格(RMB)	Price	6500.00



SK7210HP

SK7210HP		
超声(w)	Ultrasonic	350
加热(w)	Heater	390
容量(L)	Capacity	15
槽内尺寸(mm)	Tank Size(L×W×H)	330×300×150
外形尺寸(mm)	External Size(L×W×H)	390×330×310
纸箱尺寸(mm)	Carton Size(L×W×H)	457×459×412
重量(kg)	Net	9.5
	Gross	11
排水阀	Drain Valve	
标准配置	Accessories	托架 Support rack 排水软管Soft drainpipe 降音盖 Cover
价 格(RMB)	Price	8500.00



SK2510HP

SK2510HP		
超声(w)	Ultrasonic	250
加热(w)	Heater	270
容量(L)	Capacity	10
槽内尺寸(mm)	Tank Size(L×W×H)	300×240×150
外形尺寸(mm)	External Size(L×W×H)	360×270×310
纸箱尺寸(mm)	Carton Size(L×W×H)	432×367×397
重量(kg)	Net	7.7
	Gross	9
排水阀	Drain Valve	
标准配置	Accessories	托架 Support rack 排水软管Soft drainpipe 降音盖 Cover
价 格(RMB)	Price	6700.00



SK8210HP

SK8210HP		
超声(w)	Ultrasonic	500
加热(w)	Heater	520
容量(L)	Capacity	22.5
槽内尺寸(mm)	Tank Size(L×W×H)	500×300×150
外形尺寸(mm)	External Size(L×W×H)	570×330×330
纸箱尺寸(mm)	Carton Size(L×W×H)	662×431×428
重量(kg)	Net	12.8
	Gross	14.6
排水阀	Drain Valve	
标准配置	Accessories	托架 Support rack 排水软管Soft drainpipe 降音盖 Cover
价 格(RMB)	Price	10200.00



SK6210HP

SK6210HP		
超声(w)	Ultrasonic	280
加热(w)	Heater	270
容量(L)	Capacity	10.5
槽内尺寸(mm)	Tank Size(L×W×H)	500×140×150
外形尺寸(mm)	External Size(L×W×H)	570×160×310
纸箱尺寸(mm)	Carton Size(L×W×H)	660×290×425
重量(kg)	Net	8.4
	Gross	9.9
排水阀	Drain Valve	
标准配置	Accessories	托架 Support rack 排水软管Soft drainpipe 降音盖 Cover
价 格(RMB)	Price	7300.00

★合理地选用配件能使仪器达到最佳效果(见P37)

小贴士

理想的清洗液温度应控制在55~60℃，当清洗器温度上升至65~80℃时，超声波振子的内阻将增加10~20%，而功率将递减24~34%。  
Optimal cleaning temperature is 55℃ to 60℃. When temperature rises to 65℃ to 80℃, internal resistance of ultrasonic vibrator will rise by 10% to 20% and power will be 24% to 34% lower.